TABLE OF CONTENTS

To navigate to a specific date of revision, click on the date listed below.

Revision Date:

May 3, 2011 November 5, 2010

The Standard Plans for Road Construction have been revised by various changes including, but not limited to, the following:

May 3, 2011 (Back to Top)

1. **GR-2**

- a. Typical Side View detail Reference to plate washer removed resulting in a new note stating "Button Head Post Bolt".
- b. 5/8" Button Head Bolt and Recessed Nut Detail Bolt length for FBB03 changed from 10" to 9-1/2".

2. **GR-12**

a. Post Bolt Detail – Bolt length changed from 10" to 9-1/2".

3. **GR-14**

a. Post Bolt Detail – Bolt length changed from 10" to 9-1/2".

November 5, 2010 (Back to Top)

4. **DR-2**

a. Plate 3 - Reference to specific item number and size end section removed resulting in a new note stating "Appropriate steel end section".

5. **GR-11**

- a. Reference to specific item numbers throughout drawing removed resulting in removal of General Note #6 and modification to General Note #5.
- b. Side View at Splice Post Detail post length changed to **6'-6'** and embedment length changed to **3'-9"**.
- c. Plan View Post length changed from 7'-0" to **6'-6"**.

6. **GR-12**

- a. Reference to specific item numbers throughout drawing removed resulting in removal of General Note #7 and modification to General Note #5.
- b. Beam Splice Detail slot blowups adjusted to line up with detail.
- c. Side View at Splice Post Detail post length changed to **6'-6"** and embedment length changed to **3'-9**.

- d. Structural Shape Steel Post & Block Detail post length changed from 7'-0" to 6'-6"
- e. Plan View Post length changed from 7'-0" to 6'-6".

7. **GR-13**

- a. Reference to specific item numbers throughout drawing removed.
- b. General Notes Change post length reference from 6'-0" to **6'-6**" in Note #6

8. **GR-14**

- a. Reference to specific item numbers throughout drawing removed.
- b. Beam Splice Detail slot blowups adjusted to line up with detail.
- c. General Notes Change post length reference from 6'-0" to **6'-6**" in Note #7

9. **GR-15**

- a. Reference to specific item numbers throughout drawing removed.
- b. Section A-A Changed "Median" to "**Double-Faced**"
- c. Modified Section Changed "Median" to "Double-Faced"
 - i. NOTE Changed "barrels" to "lanes"
- d. General Notes Added Note #5.

10. **GR-16**

- a. Reference to specific item numbers throughout drawing removed resulting in addition of General Note #5
- b. Section A-A Changed "Median" to "**Double-Faced**"
- c. Plan & Elevation views Minor horizontal rebar addition (#6 loop bar)
- d. Material Notes Added Note #5.

11. GR-17 & GR-18

- a. Reference to specific item numbers throughout drawing removed resulting in modification of General Note #9.
- b. Plan & Elevation Views Minor graphic change line added to show transition as F-shape barrier
- c. "Median Thrie Beam Attachment" changed to "**Double-Faced** Thrie Beam Attachment"
- d. Section B-B "2'-8" (minimum)" changed to "2'-6" (minimum)" face of rail to slope break
- e. Plan Views "Single Rail" changed to "Single-Faced Thrie Beam Guardrail" and "Median Double Rail" changed to "Double-Faced Thrie Beam Guardrail"
- f. Elevation View "Median" changed to "Double-Faced"

12. **GR-19**

a. Reference to specific item numbers throughout drawing removed resulting in renumbering of General Notes:

- i. Removed old Note #2
- ii. Added new Note #5
- b. General Notes Changed reference to "25 u" to "1000 microinches"
- c. Perspective View Changed "Median" to "Double-Faced"

13. **GR-20**

- a. Reference to specific item numbers throughout drawing removed resulting in renumbering of General Notes:
 - i. Removed old Note #2
 - ii. Added new Note #5
- b. General Notes Changed reference to "25 u" to "1000 microinches"
- c. Perspective Views Changed "Median" to "**Double-Faced**"
- d. Perspective Views Minor graphic change line removed to show transition as Single Slope barrier.
- e. Replaced Section B-B to show Single Slope barrier rebar

14. **GR-21**

- a. Reference to specific item numbers throughout drawing removed resulting in addition of General Note #9.
- b. "Median Thrie Beam Attachment" changed to "**Double-Faced** Thrie Beam Attachment"
- c. Section B-B "2'-8" (minimum)" changed to "2'-6" (minimum)" face of rail to slope break
- d. Plan Views "Single Rail" changed to "Single-Faced Thrie Beam Guardrail" and "Median Double Rail" changed to "Double-Faced Thrie Beam Guardrail"
- e. Elevation View "Median" changed to "Double-Faced"

15. **GR-22**

- a. Reference to specific item numbers throughout drawing removed resulting in addition of General Note #4.
- b. "Median Thrie Beam Attachment" changed to "**Double-Faced** Thrie Beam Attachment"
- c. Section B-B "2'-8" (minimum)" changed to "2'-6" (minimum)" face of rail to slope break
- d. Plan Views "Single Rail" changed to "Single-Faced Thrie Beam Guardrail" and "Median Double Rail" changed to "Double-Faced Thrie Beam Guardrail"
- e. Elevation View "Median" changed to "Double-Faced"
- f. Plan and Elevation Views Minor graphic change lines removed to show transition as Single Slope barrier

16. **PM-3**

a. General Note #5 added clarifying thermoplastic vs. paint usage.

17. **PM-4**

a. Note added clarifying thermoplastic vs. paint usage.

18. **PM-7**

a. Reference to Word and Symbol Lane Layout Standard changed from PM-6 to **PM-8**.